

LEVEL SENSOR SUPPORTS

ACCESSORIES CYLINDER

TECHNICAL SPECIFICATIONS

They are classified according to silo connection.

Supports:

A MEMBRANE DETECTOR

This detector is installed over the bodysheet without any support

B ROTATIVE LEVEL INDICATOR SUPPORT

To connect rotative level detectors (minimum capacity)

PARTS AND MATERIALS

- Painted sheet. S275 JR e= 5mm
- Thread
- $\varnothing(\text{ext}) = 55\text{mm}$
- DIN 2986
- Female thread BSP GAS 1 1/2"

C THREADED SUPPORT FOR ROOF/ HOPPER

To hanging, capacitive or rotative detectors with extension

PARTS AND MATERIALS

- Painted sheet. S275 JR e= 3mm
- Thread
- $\varnothing(\text{ext}) = 55\text{mm}$
- DIN 2986
- Female thread BSP GAS 1 1/2" ó 1"
- To change thread 1 1/2" to 1" it's necessary an adapter

D FLANGE SUPPORT

To radar or special detectors

PARTS AND MATERIALS

- Steel sheet fixed on the roof. Galvanised sheet. S275 JR. e= 5mm
- Galvanised steel pipe. S275 JR. $\varnothing(\text{ext}) = 106\text{mm}$. e= 6mm.
- Circular steel sheet defined by the customer. Galvanised steel. S275 JR. e= 5mm
- PN 100 DR 16. Geometry according to PN 60, PN 100 ó PN 200

