ROOF INSPECTION DOOR

ACCESSORIES ROOF



FILE 5.4 **VERSION** 3. 14/06/2021

COD. ASPUERTECH



TECHNICAL SPECIFICATIONS

Door to go into the silo. Dimensions 610 x 700mm

To be installed it's necessary to open the hole over a standard roof sector.

It has a block system over the handle.

Usually it's installed with an inside ladder, but the ladder it's not a standard accessory.

It's a standard accessory that doesn't supply to the manhole.

PARTS AND MATERIALS

- 1 ROOF ACCESS DOOR FLANGE
 - · Access door's frame
 - · MATERIAL: Galvanised steel S275 JR e= 3mm
- (2) ROOF ACCESS DOOR COVER
 - · Access door's cover
 - · MATERIAL: Galvanised steel S275 JR e= 2mm
- (3) ROOF ACCESS DOOR FLANGE-HINGE
 - \cdot Bent sheet joined to roof access door flange and roof access door cover
 - \cdot MATERIAL: Galvanised steel S280 GD Z600 MAC e= 3mm
- (4) LOCK SYSTEM
 - · Simple and easy
 - · System composed of a wing nut
- (5) WEATHER STRII
 - \cdot Cover placed on the door leaf, to seal its connection with the lid
 - · MATERIAL: rubber